



SD

“Compact double rail floor conveyor”



SINGLE LINE - FLOOR CONVEYOR

CALDAN SD

With its double sided guiding system the Caldan SD floor conveyor allows an excellent accuracy in the presentation of the jigs / work pieces.

SD system advantages:

- No contamination as the work pieces are placed on top of the conveyor system.
- A very space saving solution compared to more traditional conveyor systems like belt- and roller conveyors.
- Only a minimum of maintenance and user training is required.
- Easy access to the vital parts of the conveyor system.

As with all Caldan conveyors the consequent use of tested high quality components increases functional reliability of the system.





Caldan Conveyor Solutions - simply perfect.

Specifications:

The Floor conveyor type SD consists of two Caldan standard straight profiles.

In the upper profile a cardan chain is driven by one or more drive units with fixed or variable speed. The underlying profile supports the wagon.

The wagon body consists of 0,16 inches laser cut and folded plates assembled with a minimum of welding operations.

The load capacity of the wagon is max. 66 Lbs.

The high accuracy in the positioning of the wagon is guaranteed by the four guiding wheels placed two on each side of the wagon.

Furthermore a nylon rail mounted on the top of the power profile helps the centring the wagon in, for example, the painting area.

Turning devices non-fixable or fixable in 90° or 180° positions are mounted on the top of the wagons on customer request.

Chain pitch:

7.08 / 10.62 inches

Chain bearings:

Open or sealed and greased version

Max. temperature (surroundings):

482 °F

Max. load per trolley:

66 Lbs.

Standard length, straight profile:

236.22 inches - equipped with flanges

Horizontal curves:

Degree: 90° / 45° / 30° / 15°

Radius: 12.40 / 19.68 / 27.55 / 39.37 inches

Vertical curves:

Degree (depending on work-load):

15° / 30°

Radius: 39.37 inches

All horizontal and vertical curves can be manufactured in special radii on request.

Drive unit:

Straight version, single sided caterpillar drive or 90° version with driving wheel.

Gear motor with fixed or variable speed

Tension unit:

Manual or pneumatic/ weight-loaded

Pneumatic lubrication:

Semi- or fully automatic version.

Point- or fog lubrication of the cardan chain

Special equipment:

Motorized or pneumatic turning stations

Accumulation possibilities:

None