

P&F420 - Heavy duty Power & Free conveyor system .



P&F420

POWER & FREE OVERHEAD CONVEYOR

The flexible Power & Free conveyor system with a load capacity up to 22000 Lbs (10.000 kg).

Simple and reliable accumulation of wagons in in-line, 45° and in 90° buffer zones.

Minimum accumulation distance - 15.74 inches (400 mm).


Smooth trolley transfer from one conveyor circuit to another minimizes the use of transfer units, thus lowering systems costs.

Unique trolley- and accumulation stop design ensures an instant and a highly reliable separation of wagons in the accumulating zones.

The use of modular components offers total flexibility and liberty in configuring the conveyor circuit layout.

Consequent use of tested quality components giving confidence in operation even in very harsh working environments.

Noiseless accumulation by means of non friction disengagement of the trolleys from the conveyor chain drive.





P&F420

TECHNICAL SPECIFICATIONS

The Power & Free conveyor type P&F420 consists of two CALDAN straight profiles. In the upper "Power" profile a cardan chain is driven by one or more drive units.

In the underlying "Free" profile the wagons are driven by power chain carriers, via pivotal pawls attached to the front and back of the trolley.

Both the chain carrier pitch and the accumulation distance is designed according to customer request.

The wagons can, according to handling requirement, be separated and accumulated either in line, or at 45° or 90° within accumulation zones.

When routed into a closed accumulation stop, or when reaching the "tail" of the previous trolley, the trolley's accumulation lever is lifted and the pawl units are lowered. Hereby the trolley is disengaged from the chain carriers.

<p>Chain carrier pitch: 7.08/10.62 inches (180/270 mm)</p> <p>Max. temperature (surrounding): 482 °F</p> <p>Max. load per trolley (4-wheeled): 2204 Lbs (1.000 kg)</p> <p>Max. load per wagon (load bar with 2 / 4 / 8 / 16 trolleys): 4409 / 8818 / 13230 / 22000 Lbs. (2.000 / 4.000 / 6.000 / 10.000 kg)</p> <p>Standard length, straight profile: 118.11 inches (3.000 mm)</p> <p>Trolley wheels / chain bearings: Open or sealed and greased version</p>	<p>Horizontal curves: Degree: 90° / 45° / 30° / 15° Radius: Min. 59.05 inches (1.500 mm)</p> <p>Vertical curves: Depending on work-load</p> <p>Drive unit: Straight version with double sided caterpillar drive or 90° version with driving wheel. Gear motor with fixed or variable speed</p> <p>Tension unit: Manual or pneumatic/ weight-loaded</p> <p>Switching gate: Manual, pneumatic or electrical version</p>	<p>Vertical drop- and lift section: Available in guided/ floor mounted version or unguided and suspended from the ceiling</p> <p>Accumulating stop: Pneumatic or electrical version</p> <p>Pneumatic lubrication: Semi- or fully automatic version. Point- or fog lubrication of the cardan chain and / or the trolleys</p> <p>Special designs: E.g. turning stations</p> <p>Accumulation possibilities: Automatic. In-line, 90° and 45°</p>
---	--	---